



INNER APR A HARBOR

NOTES:

1. GRADE A SWALE 800'± AT A SLOPE OF 1%. PLACE EXCAVATED MATERIAL AND FORM A BERM BETWEEN DOCKS "I" AND "J" AS SHOWN.
2. WHERE PIPE CROSSES FENCE, REMOVE ONE STRAND AND PROVIDE OPENING.
3. BURY PIPE UNDER SRF ACCESS ROADS.
4. RESTORE ROADS TO ORIGINAL CONDITION AND CLOSE FENCES WHEN PIPES ARE REMOVED.

|                        |                              |                         |                        |
|------------------------|------------------------------|-------------------------|------------------------|
| DEPARTMENT OF THE NAVY |                              | BUREAU OF YARDS & DOCKS |                        |
| PUBLIC WORKS CENTER    |                              | GUAM, M.I.              |                        |
| DES                    | PWC                          | APRA HARBOR AREA        |                        |
| DRWN P. D. MENDOK      | DREDGE SPOIL DISPOSAL PLAN   |                         |                        |
| CHK <i>[Signature]</i> | DATE 1/25/62                 |                         |                        |
| DIV DIR, Underwood     | APPROVED <i>[Signature]</i>  | PLANNING OFFICER        |                        |
| CORR ENGR              | DEPT HEAD <i>[Signature]</i> | SCALE 1"=400'           | PWC SKETCH NO SK-46-62 |
| WR NO 41242-2          | DATE 4/2/62                  |                         |                        |